

Straight Wall

Buckhorn's reusable Straight Wall Container System delivers total cost savings and efficiency throughout the supplier-to-manufacturer material handling process.

Our stack-only modular containers are ideal for closed loop shipping, in-process handling and storage applications where the same containers are used throughout.

- Containers cube 48" x 45" pallets
- Reinforced sides and bottoms enhance product protection
- Interworking sizes allow mixed stacking on pallet
- Perimeter dust skirt on select sizes for added product protection
- Compatibility with other brands to expand your existing system
- Injection molded HDPE construction for impact, moisture and chemical resistance
- Custom interior dunnage available
- Options: Lids, ID systems, dunnage, drain holes and cross-stacking bottoms



The modular design cubes the AIAG standard 48" x 45" pallet for maximum space usage.

Straight Wall Container System

Compatible with RFID Systems

Lids

Protect contents against dust, dirt and other contaminants. Attached lid option available (model SA15121002)

Straight Wall Design

Straight, smooth interior walls allow for maximum cube and easy insertion of dunnage

Reinforced Corner Ribbing

Provides maximum column strength for secure stacking



Identification Areas


Located on all four sides. Identification of contents is easy with optional cardholders, label placards, and hot stamping **See page 58 for details**

Ergonomic Handles

For enhanced comfort, efficiency and safety when lifting loaded containers

Pallet Perimeter Lip

Provides load stability and prevents container from shifting



Did You Know...?

You can use different color hot stamps for additional container identification.

Cross Cube Containers



Our **SX model Cross Cube Containers** have a special bottom-grid design that facilitates stacking of larger containers on top of smaller containers. 10 sizes available with this feature.

See page 26

- Optimize pallet space with vertically modular loads
- Improve line space usage
- Sequence parts by usage
- Reinforced bottom for secure stacking

Pallet & Top Cap Systems (See pages 10-11 for complete details)



4-way entry pallets feature:

- Dynamic weight capacity of 3,000-8,000 lbs. (varies by pallet model)*
- Perimeter lips available on each pallet
- 2-side or 4-side Pallet Lock "Seat Belt" System

*Based on equally distributed load at room temperature of 73°F (+/-5°)



Top Caps increase stability by:

- Securing top layer of palletized containers and protecting contents
- Accommodating optional Pallet Lock "Seat Belt" System to further secure stacks

Straight Wall Container System Specifications



SW12070502



SW15120602



SW151208A2
SX151208A4
w/dust skirt



SW15121002



SW24111002



SW241504A2
SX241504A4
w/dust skirt



SW24150602



SW241508A2
SX241508A4
w/dust skirt



SW24151002
SX24151000



SW241511A2
SX241511A4
w/dust skirt



SW24151502
SX24151500
w/dust skirt



SW242208A2
SX242208A4
w/dust skirt



SW242211A2
SX242211A4



SW242215A2
SX242215A4
w/dust skirt




SW48150802
SX48150800

(Not pictured SW32150802)

Model No.	Description	Dimensions					Inside Usable Height H"(F)	Weight lbs	Weight Capacity lbs	Volume Cu.Ft.	Trailer Capacity	
		L"(A)	Outside Top W"(B)	H"(C)	Inside Bottom L"(D)	W"(E)					48"	53"
SW12070502	Solid Bottom/Sides	12	7.5	5	9.38	5.44	4.38	1.2	60	0.13	10,368	11,232
		305	191	127	238	138	111	0.5	27	3.66	—	—
SW15120602	Solid Bottom/Sides	15	12	5.5	13	9.38	4.88	2.3	100	0.34	4896	5304
		381	305	140	330	238	124	1.0	45	9.75	—	—
SW151208A2	Solid Bottom/Sides	15	12	7.5	13	9.38	6.88	2.5	100	0.49	3456	3744
		381	305	191	330	238	175	1.1	45	13.75	—	—
SW15121002	Solid Bottom/Sides	15	12	9.5	13	9.38	8.88	3.5	100	0.63	2592	2808
		381	305	241	330	238	226	1.6	45	17.75	—	—
SW24111002	Solid Bottom/Sides	24	11	9.5	21.38	9.13	8.88	4.3	100	1.00	2016	2160
		610	279	241	543	232	226	2.0	45	28.41	—	—
SW241504A2	Solid Bottom/Sides	24	15	4	21.38	13	3.38	2.9	100	0.54	3456	3744
		610	381	102	543	330	86	1.3	45	15.40	—	—
SW24150602	Solid Bottom/Sides	24	15	5.5	21.38	13	4.88	3.7	100	0.78	2448	2652
		610	381	140	543	330	124	1.7	45	22.23	—	—
SW241508A2	Solid Bottom/Sides	24	15	7.5	21.38	13	6.88	4.1	100	1.11	1728	1872
		610	381	191	543	330	175	1.9	45	31.34	—	—
SW24151002	Solid Bottom/Sides	24	15	9.5	21.38	13	8.88	5.3	100	1.43	1296	1404
		610	381	241	543	330	226	2.4	45	40.45	—	—
SW241511A2	Solid Bottom/Sides	24	15	11	21.38	13	10.38	5.1	100	1.67	1152	1248
		610	381	279	543	330	264	2.5	45	47.28	—	—
SW24151502	Solid Bottom/Sides	24	15	14.5	21.38	13	13.88	6.9	100	2.23	864	936
		610	381	368	543	330	353	3.1	45	63.23	—	—
SW242208A2	Solid Bottom/Sides	24	22	7.5	21.38	20.38	6.88	5.8	100	1.73	1152	1248
		610	559	191	543	518	175	2.6	45	49.13	—	—
SW242211A2	Solid Bottom/Sides	24	22	11	21.38	20.38	10.38	7.6	100	2.62	768	832
		610	559	279	543	518	264	3.4	45	74.12	—	—
SW242215A2	Solid Bottom/Sides	24	22	14.5	21.38	20.38	13.88	8.9	100	3.50	576	624
		610	559	368	543	518	353	3.9	45	99.12	—	—
SW32150802	Solid Bottom/Sides	32	15	7.5	29.38	13	6.88	5.6	100	1.52	1152	1248
		813	381	191	746	330	175	2.5	45	43.07	—	—
SW48150802	Solid Bottom/Sides	48	15	7.5	45.38	13	6.88	7.5	100	2.35	864	936
		1219	381	191	1153	330	175	3.4	45	66.52	—	—

Capacity is dependent upon application and use environment. Check with Buckhorn for suitability in your application. Specifications subject to change without notice. All dimensions are approximate.

Straight Wall Containers




- Stock Color: Dark Gray
- Models SW15120602, SW151208A2, SW24150602, and SW241508A2 also available in Green, Dark Blue
- Other colors available, minimum order required

= In Stock Items



Straight Wall Container System Specifications

Cross Cube Containers



- Stock Color: Dark Gray
- Other colors available, minimum order required

Model No.	Description	Dimensions				Inside Usable Height H"(F)	Weight lbs	Weight Capacity lbs	Volume Cu.Ft.	Trailer Capacity	
		L"(A)	Outside Top W"(B)	H"(C)	Inside Bottom L"(D)					W"(E)	48'
SX151208A4	Solid Bottom/Sides	15	12	7.5	13	9.38	2.8	100	0.45	3456	3744
	mm/kg/m ³ /l	381	305	191	330	238	162	1.3	45	12.75	—
SX241504A4	Solid Bottom/Sides	24	15	4	21.38	13	2.88	3.5	100	3456	3744
		610	381	102	543	330	73	1.6	45	13.12	—
SX241508A4	Solid Bottom/Sides	24	15	7.5	21.38	13	6.38	4.6	100	1728	1872
		610	381	191	543	330	162	2.1	45	29.06	—
SX24151000	Solid Bottom/Sides	24	15	9.5	21.38	13	8.38	6.2	100	1188	1404
		610	381	241	543	330	213	2.8	45	38.17	—
SX241511A4	Solid Bottom/Sides	24	15	11	21.38	13	9.88	5.9	100	1152	1248
		610	381	279	543	330	251	2.7	45	45.00	—
SX24151500	Solid Bottom/Sides	24	15	14.5	21.38	13	13.38	7.6	100	864	936
		610	381	368	543	330	340	3.4	45	61.86	—
SX242208A4	Solid Bottom/Sides	24	22	7.5	21.38	20.38	6.38	6.3	100	1152	1258
		610	559	191	543	518	162	2.9	45	45.60	—
SX242211A4	Solid Bottom/Sides	24	22	11	21.38	20.38	9.88	8.0	100	768	832
		610	559	279	543	518	251	3.6	45	70.55	—
SX242215A4	Solid Bottom/Sides	24	22	14.5	21.38	20.38	13.38	9.1	100	576	624
		610	559	368	543	518	340	4.1	45	95.55	—
SX48150800	Solid Bottom/Sides	48	15	7.5	45.38	13	6.38	8.9	100	864	936
		1219	381	191	1153	330	162	4.0	45	61.68	—

Capacity is dependent upon application and use environment. Check with Buckhorn for suitability in your application. Specifications subject to change without notice. All dimensions are approximate.

Lids Straight Wall & Cross Cube

- Stock Color: Dark Gray

Model No.	Description	Dimensions Outside Top		Straight Wall Footprint
		L"	W"	
SL15120100	Injection Molded	15	12	15" x 12"
	mm/kg	381	305	
SL24150100	Injection Molded	24	15	24" x 15"
		610	381	
SL24220100	Injection Molded	24.03	22.06	24" x 22"
		610.3	560	


Label Placard & Card Holders

Identification Systems for Straight Wall Containers	Model Number
Self-Adhesive Clear Plastic Card Holder for 4.5" x 3.5" Card	04ACCH029473C00
Self-Adhesive Clear Plastic Card Holder for 6" x 4" Card	04ACCH029483C00
Kanban Style Card Holder, 8.25" x 4.25"	0804CHMX0200003
Label Placard, 4.5" x 6.5"	04ACLPK00109


Reference page 58 for images

NR = Not Rackable unless fully supported
See page 9 to learn more.

See pages 6-11 for complete pallet line



Pallets




- Stock Color: Black
- Solid and vented decks
- 4-way entry
- Structural foam
- See page 10 for more pallet details

Model No.	Description	Dimensions				Weight lbs.	Weight Capacity			Fork Tunnel Dimensions			Return Ratio	Truck Capacity			
		L"(A)	External W"(B)	H"(C) [†]	Internal L"(D)		W"(E)	Static lbs.	Dynamic lbs.	Rack lbs.	long side L"(G)	H"(H)		short side L"(I)	H"(J)	48'	53'
PM32300632	32"x30" 1" Lip	32	30	6	31.40	29.4	25.7	20,000	3000	N/R	9	3.7	8.7	3.7	1:1	864	960
	mm/kg	813	762	152	798	747	11.7	9074	1361	N/R	229	94	221	94	—	—	—
PW48400622	48"x40" 1/2" Lip	47.62	39.75	6.38	45.87	38	42.35	20,000	7000	2500	11.75	3.38	10.38	3.38	1:1	420	450
		1210	1010	162	1165	965	19.2	9074	3176	1134	298	86	264	86	—	—	—
PO48450632	48"x45" 3/4" Lip	48.75	45.75	6	48	45	58	30,000	3000	N/R	13.12	3.65	13.45	3.65	1:1	408	442
		1238	1162	152	1219	1143	28.6	13,612	1361	N/R	333	93	343	93	—	—	—
PR48450533	48"x45" 1" Lip	49	45.75	5	48	44.75	63	32,000	8000	N/R	8.75	3.5	11.2	3.5	1:1	360	390
		1245	1162	127	1219	1137	29	14,519	3630	N/R	222	89	284	89	—	—	—
PW48450622	48"x45" 1/2" Lip	47.62	44.75	5.87	45.87	43.25	45.31	20,000	7000	2500	11.88	3.38	10.38	3.38	1:1	360	390
		1210	1137	149	1165	1099	21	9074	3176	1134	302	86	264	86	—	—	—

[†]Height to deck. Capacity is dependent upon application and use environment. Check with Buckhorn for suitability in your application. Specifications subject to change without notice. All dimensions are approximate.

Top Caps



- Stock Color: Black
- Optional seat belt systems to secure loads
- See page 10 for more pallet details

Model No.	Description	Dimensions				Top Cap Weight lbs.	Return Ratio	Compatible Pallet	
		L"(A)	External W"(B)	H"(C)	Internal L"(D)	W"(E)			
TM32300300	32"x30" (SF)	33	31	2.5	32.5	31.5	9.8	1:1	PM32300632
	mm/kg	838	787	64	826	800	4	—	—
TW48400200	48"x40" (SF)	48.56	40.63	2.25	48.17	40.24	22.9	1:1	PW48400622
		1233	1032	57	1224	1022	10	—	—
TO48450300	48"x45" (SF)	49.13	46.13	2.75	48.38	45.38	25	1:1	PO48450632, PR48450533
		1248	1172	70	1229	1153	11	—	—
TV48450300	48"x45" (VF)	49	46	3	48.5	45.5	15	1:1	PO48450632, PR48450533
		1245	1168	76	1232	1156	7	—	—
TR48450200	48"x45" (SF)	49	46	2	48.5	45.5	22	1:1	PO48450632, PR48450533
		1245	1168	56	1232	1156	10	—	—
TW48450200	48"x45" (SF)	48.63	45.63	2.25	48.24	45.23	24.8	1:1	PW48450622
		1235	1159	57	1225	1149	11	—	—

(SF) = Structural Foam (VF) = Vacuum Formed
Capacity is dependent upon application and use environment. Check with Buckhorn for suitability in your application. Specifications subject to change without notice. All dimensions are approximate.

S = In Stock Items